

F15 Mono Color LED Linear Flex

F15-24V-3528-72-2200K-6500K

Specification



Dimension

Emitting Surface

Horizontal Bending

Min. Bending Diameter

Beam Angle

Ansi C78.377

Ansi C78.377

SDCM < 3

One Bin

Dimmable

Submersible

Ambient Temp.

Class 3

LM-80

IK08

UV Resistant

Flame Resistant

Saltwater Resistant

Solvents Resistant

Dirt Resistant

CE

RoHS

UL Listed

CB

3 years warranty




Warranty

Technical Parameters

| Electrical | |
|-----------------------|--|
| Input Voltage | 24V DC |
| Power Consumption | 5W/m |
| Physical | |
| LED Count | 72 LEDs/m |
| Cutting Unit | 12 LEDs |
| Cutting Unit Length | 166.7mm |
| Minimum Bend Diameter | 80mm |
| Output | |
| LED Light | Epistar SMD LED 3528 |
| CRI | >80, >90 |
| Max Run Length* | |
| Single Feed | 15M |
| Double Feed | 30 M |
| Beam Angle | 120° |
| Lumen Maintenance | 70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C |
| Temperature Ranges | |
| Installation | 0°C to 50°C |
| Operating | -25°C to 50°C |
| Dependability | |
| Warranty | 3 Years Warranty |
| IP Rating | IP68 Wet location submersible <2m |

| Optional Color | Lumen Output |
|----------------|--------------------------|
| | 2200K(2238±102K) 127lm/m |
| | 2700K(2725±145K) 130lm/m |
| | 3000K(3045±175K) 130lm/m |
| | 3500K(3465±245K) 130lm/m |
| | 4000K(3985±275K) 142lm/m |
| | 4500K(4503±243K) 145lm/m |
| | 5000K(5029±283K) 150lm/m |
| | 6500K(6532±510K) 160lm/m |
| | Green(520-530nm) 119lm/m |
| | Blue (455-465nm) 20lm/m |
| | Red (620-630nm) 45lm/m |
| | Pink(610-620nm) 53lm/m |
| | Amber(585-595nm) 37lm/m |
| | Orange(595-605nm) 35lm/m |

Illuminance Distribution



F15 Mono Color LED Linear Flex

Connection

